



Plastic & polymer additives and solution supplier
E:info@novistagroup.com I : www.novistagroup.com

Technical Data Sheet

ProFlame®SI760

SI760 is silicone flame retardant which can combine with phosphate, sulfonate or brominated flame retardant to improve the flame retardant efficiency by 10-30%. It has better compatibility with polymer and allows higher adding amount to get better flame retardant performance.

Tech Spec:

Item	Index
Appearance	White powder
Main content	≥99.5%
Iron	≤5ppm
Moisture	≤1.0%
PH value(5% in water)	6.5-7.0
TGA(5% Weight Loss)	≥350°C

Usage:

As synergistic flame retardant, its dosage is around 0.5-1.5%.

- ▶ It can be used in conjunction with KSS to make flame-retardant PC.
- ▶ When used in conjunction with phosphate flame retardants, the addition of the main flame retardant can be reduced by 10-30%, such as TPP, BDP, RDP, etc
- ▶ When used in combination with traditional brominated flame retardants, the addition of main flame retardants can be reduced by 10-30%.

Packing:

Net weight: 20kg/ bag or 20kg/drum.

It is not dangerous cargo. You should handle the material according to the instruction described on MSDS. The MSDS is available from sales department once required.

+86-536-8206760 info@novistagroup.com www.novistagroup.com

The information presented herein is believed to be accurate and reliable, but is presented without guarantee or responsibility on the part of Novista Group and its subsidiaries. It is the responsibility of the user to comply with all applicable laws and regulations and to provide for a safe workplace. The user should consider any health or safety hazards or information contained herein only as a guide, and should take those precautions which are necessary or prudent to instruct employees and to develop work practice procedures in order to promote a safe work environment. Further, nothing contained herein shall be taken as an inducement or recommendation to manufacture or use any of the herein materials or processes in violation of existing or future patent.